



150W

ALL IN ONE LED SOLAR LIGHTING SOLAR ARMATÜR (ALL IN ONE)

- 100% Autonomy with solar energy
- Integrated design – All In One
- Internal battery
- Light and durable
- IP65 (Water proof)
- Long life battery
- Body Material: Aluminum with corrosion resistance
- Presence sensor with human induction, greater sensitivity and control
- Solar enerji ile 100% bağımsız enerji
- Entegre tasarım-Hepsi bir arada
- Entegre batarya
- Aydınlık ve dayanıklılık
- IP65 (su geçirmez)
- Uzun ömürlü batarya
- Korozyona dayanıklı Alüminyum gövde
- Yüksek hassasiyetli varlık sensörü



90x22x4,5 cm





150W

ALL IN ONE LED SOLAR LIGHTING SOLAR ARMATÜR (ALL IN ONE)

| | |
|---------------------|-----------------------|
| LED Power | 150W |
| Battery | LifePO4 3.2V 50AH |
| Solar Panel | Poly 10V25W |
| Led Chip | USA BRIDGELUX CHIP |
| Charging Time | 8-10H |
| Working Time | 2 rainy days |
| Input Voltage | DC 12V |
| Beam Angle | 120° |
| Light Efficiency | 120 lm/w |
| PIR Sensor | YES |
| Dimmable | NO |
| Remote Control | YES |
| CCT | 6000K-6500K |
| Fixture Material | Aluminum Alloy |
| Glass | Step-Tempered Glass |
| IP Rating | IP65 |
| Average Lifespan | 50000 hours (for LED) |
| Discharge Time | 18-20H |
| Sensor Distance | 6-8 M |
| Installation Height | 8-10 M |
| Lamp Body Material | Aluminum |

PERFORMANCE

- Optics designed for squares and parks
- Easy to transport and install
- Comes with clamps and screws for fixing on poles

| | |
|----------------------------|---------------------------|
| LED Gücü | 150W |
| Batarya | LifePO4 3.2V 50AH |
| Solar Panel | Poly10V25W |
| Led | USA BRIDGELUX CHIP |
| Şarj Süresi | 8-10 saat |
| Çalışma Süresi | 2 yağışlı gün |
| Giriş Gerilimi | DC 12V |
| Işık Açısı | 120° |
| Işık Verimliliği | 120 lm/w |
| Hareket Sensörü | VAR |
| Ayarlanabilir Işık Şiddeti | YOK |
| Uzaktan Kontrol | VAR |
| CCT | 6000K-6500K |
| Bağlantı Malzemesi | Alüminyum Alaşımları |
| Cam | Temperlenmiş Cam |
| IP Sınıfı | IP65 |
| Ortalama Ömür | 50000 saat (LED'ler için) |
| Deşarj Süresi | 18-20 saat |
| Sensör Mesafesi | 6-8 M |
| Kurulum Yüksekliği | 8-10 M |
| Lamba Gövde Malzemesi | Alüminyum |

ÖNEMLİ NOKTALARI

- Meydan ve parklar için tasarlanmış optikler
- Taşıma ve kurulum kolaylığı
- Direklere sabitlemek için kelepçeler ve vidalar ile birlikte gelir.

